

Digital Theatre Timers Clock & Interval Timer

Model 936211DT

Features

- Stainless steel casing (IP54) with mineral glass protection
- Flush mounting with 4 holes (screws not included)
- Adjustable brightness (4 levels)
- Angle of vision: 120°
- Silent operation
- Digit made of 7 segments with 3 LED each
- Power supply: 230V±10%, 50/60 Hz
- Consumption: 55mA
- Operating Temperature: 0 to 50°C
- Weight: 6kg
- 936211DT includes 1 x Control Unit & Digital Timer and a Digital Clock.
- Clock & Timer are mounted individually.

Technical features of the control unit:

- Chronometer hour-minute-second from 0 to 23:59:59
- Waterproof control unit with touch sensitive keys for easy cleaning: Time Display key with LED indicator
- Start/stop key: successive pressing to start or stop the chronometer
- Reset key: resetting to zero of the chronometer
- Connection to Timer with a 2-pair telephone cable 0.5mm.Max length: 20M
- Supplied with power by the clock
- The control unit can control up to 10 clocks
- Operating temperature: 0 to 50°C
- Protection index of the front face: IP55

Simplex **Model 936211DT Theatre Timer** is for use in hospital delivery rooms, operating rooms and laboratories. The dual theatre timer is designed to keep track of VITAL timed events through out operation by providing surgeons & support staff with both interval time and accurate reference and" Real Time".

Operation

Simplex **Model 936211DT Theatre Timer** includes a Digital Timer [Model 936211DT] and a Control Unit. Manual operation is done through the control Unit Start/stop key: successive pressing to start or stop the chronometer

The Digital Clock must be connected to a Simplex Master Clock for Time synchronization

Digital Clock



936211DT



Control Unit

Contact us

Website: www.simplextime.com.au
Email: simplextime.au@tycoint.com

Phone: 13 14 91 (Australia)
+61 2 9638 8340 (International)
Document: 936211DT Digital Theatre Timers Datasheet
Issued: Feb 2009